



SP-30/200PA

Order No.: 10.3350

Price upon request

PRODUCTINFOS

PA bass-midrange speaker, 200 W, 8 Ω

- For a deep low limit frequency
- For bass-midrange applications and monitoring in bass-reflex cabinets of medium size

TECHNICAL SPECIFICATIONS

SP-30/200PA

Impedance (Z)	8 Ω
Frequency range	f3-4,500 Hz
Resonant frequency (fs)	44 Hz
Power rating	200 W
Peak music power output	400 W
Sensitivity	97 dB/W/m
Suspension compl. (Cms)	0.29 mm/N

SP-30/200PA

Moving mass (Mms)	44 g
Mech. Q factor (Qms)	6.71
Electr. Q factor (Qes)	0.41
Total Q factor (Qts)	0.39
Equivalent volume (Vas)	120 l
DC resistance (Re)	6.5 Ω
Force factor (BxL)	13.9 Tm
Voice coil induct. (Le)	0.9 mH
Voice coil diameter	\varnothing 51 mm
Voice coil former	Kapton
Linear excursion (X_{MAX})	\pm 2.5 mm
Eff. cone area (Sd)	540 cm ²
Magnet weight	1.3 kg
Magnet diameter	\varnothing 156 mm
Mounting cutout	\varnothing 279 mm
Mounting depth	132 mm
Dimensions	\varnothing 310 mm x 138 mm
Outside diameter	\varnothing 310 mm
Width	\varnothing 310 mm
Depth	138 mm
Admiss. ambient temp.	0-40 °C
Weight	4.32 kg
Sales unit	1
Type of speaker	12"