


54/7410
54H/74H10
54S/74S10
54LS/74LS10
 TRIPLE 3-INPUT NAND GATE


CONNECTION DIAGRAMS
PINOUT A



ORDERING CODE: See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0\text{ V} \pm 5\%$, $T_A = 0^\circ\text{ C to } +70^\circ\text{ C}$	$V_{CC} = +5.0\text{ V} \pm 10\%$, $T_A = -55^\circ\text{ C to } +125^\circ\text{ C}$	
Plastic DIP (P)	A	7410PC, 74H10PC 74S10PC, 74LS10PC		9A
Ceramic DIP (D)	A	7410DC, 74H10DC 74S10DC, 74LS10DC	5410DM, 54H10DM 54S10DM, 54LS10DM	6A
Flatpak (F)	A	74S10FC, 74LS10FC	54S10FM, 54LS10FM	3I
	B	7410FC, 74H10FC	5410FM, 54H10FM	

PINOUT B



INPUT LOADING/FAN-OUT: See Section 3 for U.L. definitions

PINS	54/74 (U.L.) HIGH/LOW	54/74H (U.L.) HIGH/LOW	54/74S (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
Inputs	1.0/1.0	1.25/1.25	1.25/1.25	0.5/0.25
Outputs	20/10	12.5/12.5	25/12.5	10/5.0 (2.5)

DC AND AC CHARACTERISTICS: See Section 3*

SYMBOL	PARAMETER	54/74		54/74H		54/74S		54/74LS		UNITS	CONDITIONS	
		Min	Max	Min	Max	Min	Max	Min	Max		$V_{IN} = \text{Gnd}$ $V_{IN} = \text{Open}$	$V_{CC} = \text{Max}$
I_{CCH}	Power Supply	6.0		12.6		12		1.2		mA		
I_{CCL}	Current		16.5		30		27		3.3			
t_{PLH} t_{PHL}	Propagation Delay	22		10		2.0	4.5	15		ns	Fig. 3-1, 3-4	
		15		10		2.0	5.0	15				

*DC limits apply over operating temperature range; AC limits apply at $T_A = +25^\circ\text{ C}$ and $V_{CC} = +5.0\text{ V}$.