

GORE₋₋ Leaky Feeder Antennas

Improve In-Flight Connectivity to Wireless Networks

Today's airline passengers expect to have easy access to Internet servers, email, and in-flight entertainment while airborne. GORE[™] Leaky Feeder Antennas improve signal propagation while reducing the amount of hardware required on the plane. These antennas provide reliable connectivity to different wireless systems, including picocells for mobile phone coverage and access points for airborne Wi-Fi. Ideal for both wide-body and single-aisle passenger aircrafts, Gore's antennas significantly reduce dead spots, enabling passengers to connect to wireless networks throughout the cabin.

The inherently flame-retardant materials used in the construction of GORE[™] Leaky Feeder Antennas meet the flame and smoke toxicity specifications of FAR Part 25.1359(d) and Airbus ABD0031 without added flame retardants.

TYPICAL APPLICATIONS

- Wide-body aircraft
- Single-aisle aircraft
- Picocells for mobile phone coverage
- Wi-Fi 802.11 a/b/g/n/ac and WiMAX
- Connectivity to Bluetooth, DECT, DECT2, Globalstar, GSM, IRIDIUM Sat, MMS, PDC, and TETRA protocols

| | Properties | LFA280 | LFA355 | LFA500 |
|------------|----------------------------------|---|--------|--------|
| ELECTRICAL | Operating Voltage (V RMS) | 300 | | |
| | Impedance (ohms) | 50 +5/-2 | | |
| | Frequency Range (MHz) | 400 to 6000 | | |
| MECHANICAL | Nominal Cable Diameter (mm) | 6.5 | 8.1 | 11.7 |
| | Minimum Bend Radius (mm) | 40 | 50 | 70 |
| | Operating Temperature Range (°C) | -55 to 85 | | |
| | Maximum Weight (g/m) | 72 | 85 | 153 |
| | Flame and Smoke Toxicity | Airbus ABD0031 and FAR Part 25.1359(d) | | |

TABLE 1: PRODUCT SPECIFICATIONS



Benefits of GORE[™] Leaky Feeder Antennas

- Uniform signal propagation for wireless access throughout the entire cabin
- Reliable access across a broad range of frequencies with a single antenna
- Reduced costs with single hardware set and cables that require no maintenance for the lifetime of the aircraft
- Outstanding flame and smoke protection with inherently flame-retardant materials
- Easy installation for new production and retrofit applications in both single-aisle and wide-body aircraft
- Increased flexibility with rugged cut-resistant and abrasion-resistant construction
- Reduced exposure to wireless radiation

IMPROVED CONNECTIVITY

GORE[™] Leaky Feeder Antennas provide consistent connectivity across a broad frequency range — from 400 megahertz up to 6 gigahertz — making the antennas compatible with numerous communication standards.



GORE₋₋ Leaky Feeder Antennas

With a single antenna installed along the length of the cabin, passengers can access wireless networks for their laptops, tablets, mobile phones, and in-flight entertainment systems regardless of their location in the cabin. These antennas dramatically reduce dead spots because of the proprietary technology that maintains excellent antenna gain and coupling loss over a broad range of frequencies and antenna lengths (Figures 1-6) as measured according to IEC 61196-4, Free Space Method.



FIGURE 1: ANTENNA GAIN — GORE™ LEAKY FEEDER ANTENNA 355

FIGURE 2: COUPLING LOSS — GORE[™] LEAKY FEEDER ANTENNA 355







FIGURE 3: ANTENNA GAIN — GORE[™] LEAKY FEEDER

FIGURE 5: ANTENNA GAIN — GORE™ LEAKY FEEDER ANTENNA 500



DURABLE CONSTRUCTION

The engineered fluoropolymers used in the construction of GORE[™] Leaky Feeder Antennas are inherently flame-retardant. They meet Airbus ABD0031 and FAR Part 25.1359(d) specifications for flame and smoke toxicity, which ensures reliable flame protection. These materials are also resistant to abrasion and cut-through, reducing the potential for damage during installation.

REDUCED COSTS FOR WIRELESS ACCESS

Broadband technology used in aircraft generally requires separate equipment for each wireless protocol. GORE™ Leaky Feeder Antennas enable integrated hardware to run multiple protocols through a single antenna, reducing the quantity of wireless-N access points (N-WAPs) required to ensure signal coverage. These lightweight antennas reduce equipment costs by offering a single solution that provides connectivity for a variety of electronic devices. Because of their durable construction,

FIGURE 4: COUPLING LOSS — GORE[™] LEAKY FEEDER ANTENNA 280



FIGURE 6: COUPLING LOSS — GORE[™] LEAKY FEEDER ANTENNA 500



GORE[™] Leaky Feeder Antennas do not require any maintenance for the life of the aircraft, further reducing operating costs.

ORDERING INFORMATION

GORE[™] Leaky Feeder Antennas are available in a variety of diameters, lengths, and constructions. For assistance in selecting the right antennas for your application, contact your Gore sales associates or visit gore.com.



GORE₋₋ Leaky Feeder Antennas

NOTICE — USE RESTRICTIONS APPLY Not for use in food, drug, cosmetic or medical device manufacturing, processing, or packaging operations.

GORE and designs are trademarks of W. L. Gore & Associates ©2013 W. L. Gore & Associates GmbH. PLFWI2131 REV A 01-13

